



SBLM-2-1x## Message Signs



Model	Description	Enclosure Size (W x H x D)	Actual Character Height
SBLM-2-1x8	A single Line of eight Characters	15.5" x 4.75" x 8.375"	1.7"
SBLM-2-1x16	A single Line of sixteen Characters	27.5" x 4.75" x 8.375"	1.7"
SBLM-2-1x24	A single Line of twenty-four Characters	39.5" x 4.75" x 8.375"	1.7"

SBLM-2-2x## Message Signs



Model	Description	Enclosure Size (W x H x D)	Actual Character Height
SBLM-2-2x8	Two Lines of eight Characters	17.4" x 8.4" x 9.5"	1.7" small / up to 4" large
SBLM-2-2x16	Two Lines of sixteen Characters	29.75" x 8.4" x 9.5"	1.7" small / up to 4" large
SBLM-2-2x24	Two Lines of twenty-four Characters	41.4" x 8.4" x 9.5"	1.7" small / up to 4" large

All SBLM-2-#x## Message signs can run off of RS232, RS422, RS485, current loop active, and current loop passive. Each model can accept AC voltages from 110-240 volts by default and optionally can be run off of DC voltage when specified at time of order. Optional UL models and Wireless models are also available.

toll-free **800.814.4053**
 local **909.793.8457**
 fax **909.798.4457**

2015 West Park #3
 P.O. Box 8891
 Redlands, CA 92373

www.matko.com

